



- NOTES:
1. DISTANCE BETWEEN SCORE LINES NOT TO EXCEED 5' IN LONGITUDINAL & TRAVERSE DIRECTION IN SIDEWALK.
 2. 1/4" TRANSVERSE EXPANSION JOINTS AT 20' INTERVAL FOR SIDEWALK.
 3. 1/4" TRANSVERSE EXPANSION JOINTS AT 60' INTERVAL FOR CURB & GUTTER.
 4. EXPANSION JOINTS IN SIDEWALK TO BE ADJACENT TO EXPANSION JOINTS IN CURB & GUTTER.
 5. CURB & GUTTER TO HAVE 1" SCORE AT 10' INTERVALS.
 6. AREA BETWEEN SIDEWALK AND PROPERTY LINE SHALL BE FILLED WITH CLEAN TOP SOIL FREE OF DEBRIS.
 7. PROVIDE 4" MIN. CLASS 2 AGGREGATE BASE AT 95% COMPACTION OVER NATIVE SOIL PROCESSED TO 2% ABOVE OPTIMUM MOISTURE CONTENT COMPACTED TO 90% RELATIVE DENSITY.

SIDEWALKS CURB & GUTTER

DATE	REVISIONS	BY
05/03	UPDATE CONSTRUCTION NOTES	DLS

CITY OF BIGGS	
STANDARD DETAIL	
204	
DAVID L. SWARTZ, P.E. APPROVED	1/97 DATE